



- Kanalschalldämpfer
- 20 mm SBM-Rahmen
- hohe Einfügungsdämpfung

Typ	Art. Nr.	VL m ³ /h	Δp	Dicke (d)	Spalt (s) Kulissen	Anzahl	B mm	H mm	L mm
KSD 30/15	1990	500	20	150	150	1	300	150	1000
KSD 40/20	1992	1000	20	200	200	1	400	200	1000
KSD 50/25	2003	1300	23	100	67	3	500	250	1000
KSD 50/30	2004	1600	32	100	67	3	500	300	1000
KSD 60/30	2005	2000	16	150	150	2	600	300	1000
KSD 60/35	1994	2400	20	150	150	2	600	350	1000
KSD 70/40	1996	3100	32	200	150	2	700	400	1000
KSD 80/50	1998	4300	17	200	200	2	800	500	1000
KSD 100/50	2007	6000	20	100	100	5	1000	500	1000

Einfügungsdämpfungsmass $D_{e,okt}$ [dB]

	f_m (Hz)							
	63	125	250	500	1000	2000	4000	8000
KSD 30/15	3	6	12	24	30	24	14	9
KSD 40/20	2	5	11	22	25	18	11	7
KSD 50/25	4	6	14	24	40	43	30	23
KSD 50/30	4	6	14	24	40	43	30	23
KSD 60/30	3	6	12	24	30	24	14	9
KSD 60/35	3	6	12	24	30	24	14	9
KSD 70/40	3	6	12	24	30	24	14	9
KSD 80/50	2	5	11	22	25	18	11	7
KSD 100/50	4	4	9	19	34	34	22	15